



## **Pure Turpentine Product Information Sheet**

## Description

Bartoline Pure Turpentine is an organic solvent particularly favoured by artists for use with oil-based paints as a cleaner and thinner. It is manufactured from the distillate, which is exuded from pine trees.

#### **Directions**

#### **Paint Thinning**

Add Pure Turpentine to paint as per paint manufacturer's instructions. Stir well to ensure thorough dispersion of product.

## **Brush Cleaning**

When cleaning brushes use a non-plastic container such as a paint kettle or jar. Remove as much paint as possible using a cloth or newspaper. Dip the brush into Bartoline Pure Turpentine and work in well, then rinse thoroughly with soapy water and dry with a clean cloth.

## **Cleaning Paint Spills**

To clean up paint spills, test a small patch of textiles for suitability and colour fastness. Pour a quantity of Pure Turpentine onto a suitable cloth and wipe the surface until all paint has been removed.

#### **Health and Safety**

See MSDS for full information.

**DANGER** Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled.

Toxic to aquatic life with long lasting effects.

## **Technical Data**

Measurement	Value	Test Method		
Physical State	Liquid	Visual		
Colour	Colourless	Visual		
Odour	Pine Like			
Density	0.855 – 0.868g/m3	ASTM D 233-11		
<b>Boiling Point</b>	156 - 170°C	ASTM D 233-13		
Flash point	34 - 38°C	ASTM D 56		
Viscosity	1.5 cp @ 25°C			
Kauri Butanol value	71 approx			

# **Packing Specification**

Pack Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	<u>Ti</u>	<u>Hi</u>
250ml	19594890	5010789594893	05010789806903	12	174	2088	29	6
500ml	19595000	5010789595005	05010789222697	6	195	1170	39	5

## **Customs Tariff Code**

3805 1010

# **Shipping Classification**

**Correct Shipping Name: Turpentine** Classification: Class 3 **UN Number: UN 1299** Ш

Packing Group:

Flash Point: 34 Degrees Celsius

**Additional Information: Marine Pollutant**