

TECHNICAL DATA SHEET

STOKES THINNERS XYLENE

| | | | | |
|------------------|--------------------|----------------------|-----------------|--------------------|
| Reference | Revision No | Revision Date | Printed | Page 1 of 1 |
| TH012 | 2 | 10 May 1996 | 21 October 2009 | |

| | |
|------------------------------|--|
| Properties and Uses | Stokes TH012 Thinners will thin most common industrial paints, varnishes and lacquers. It will not, however, thin cellulose, vinyl or epoxy resins or any resin which is soluble in Methylated Spirits (Ethyl Alcohol). It is classed as a flammable liquid. It may be used as a cleaning solvent for application equipment, stirrers and minor spills. Stokes TH012 Thinners will thin Stokes Quick Drying Enamels, Quick Drying Metal Primers, Chlorinated Rubbers, Hammer Finishes etc. Also suitable as a degreasing solvent. |
| Technical Data | TYPE: Aromatic hydrocarbon. (Xylene). |
| Stock Container Sizes | 2½ Litres, 5 Litres, 25 Litres and 200 Litres. |
| Storage | Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of MSDS TH012.) |
| Health and Safety | THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. TH012 FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING MEASURES, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL. |
| Thinners Disclaimer | Some of our thinners contain duty-free hydrocarbon oil, accordingly none of these solvents/thinners may be put to an ineligible use i.e as motor fuel or as an additive or extender to motor fuel or heating fuel. They are not designed nor are they suitable for such purposes. |
| Disclaimer | <p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p> |